

Borehole

**10-02-06****Log Event A****Borehole Information**

Farm : <u>A</u>	Tank : <u>A-102</u>	Site Number : <u>299-E25-86</u>
N-Coord : <u>41,158</u>	W-Coord : <u>47,714</u>	TOC Elevation : <u>689.42</u>
Water Level, ft :	Date Drilled : <u>4/30/1962</u>	

**Casing Record**

Type : <u>Steel-welded</u>	Thickness, in. : <u>0.280</u>	ID, in. : <u>6</u>
Top Depth, ft. : <u>0</u>	Bottom Depth, ft. : <u>90</u>	

Cement Bottom, ft. : 90      Cement Top, ft. : 0

**Borehole Notes:**

Borehole 10-02-06 was originally drilled in April 1962 and completed to a depth of 75 ft with 6-in.-diameter casing. In 1978, the borehole was deepened to a completed depth of 85 ft. The drive barrel was lost at a depth of 90 ft, hence the shallow completion depth. A starter casing of unknown dimensions (but assumed to be 8-in. diameter) was temporarily installed to an unknown depth. Nine gal of grout was added to the bottom of the borehole. There is no mention in the driller's log that the casing was perforated.

"As-built" drawings for the A Tank Farm indicate the original borehole was constructed with 6-in., schedule-30 pipe; however, this type of pipe was not identified in applicable engineering references. The casing thickness for the borehole is assumed to be 0.280 in., on the basis of the published thickness for schedule-40, 6-in. casing.

The top of the casing is the zero reference for the log. The casing lip is approximately 6 in. above the ground surface.

**Equipment Information**

Logging System : <u>2</u>	Detector Type : <u>HPGe</u>	Detector Efficiency: <u>35.0 %</u>
Calibration Date : <u>10/1996</u>	Calibration Reference : <u>GJO-HAN-13</u>	Logging Procedure : <u>P-GJPO-1783</u>

**Logging Information**

Log Run Number : <u>1</u>	Log Run Date : <u>11/07/1996</u>	Logging Engineer: <u>Bob Spatz</u>
Start Depth, ft.: <u>0.0</u>	Counting Time, sec.: <u>100</u>	L/R : <u>L</u> Shield : <u>N</u>
Finish Depth, ft. : <u>31.5</u>	MSA Interval, ft. : <u>0.5</u>	Log Speed, ft/min.: <u>n/a</u>

Borehole

**10-02-06****Log Event A**

Log Run Number :	<u>2</u>	Log Run Date :	<u>11/07/1996</u>	Logging Engineer:	<u>Bob Spatz</u>
Start Depth, ft.:	<u>30.5</u>	Counting Time, sec.:	<u>100</u>	L/R : <u>L</u>	Shield : <u>N</u>
Finish Depth, ft. :	<u>40.0</u>	MSA Interval, ft. :	<u>0.5</u>	Log Speed, ft/min.:	<u>n/a</u>

Log Run Number :	<u>3</u>	Log Run Date :	<u>11/08/1996</u>	Logging Engineer:	<u>Bob Spatz</u>
Start Depth, ft.:	<u>86.5</u>	Counting Time, sec.:	<u>100</u>	L/R : <u>L</u>	Shield : <u>N</u>
Finish Depth, ft. :	<u>39.0</u>	MSA Interval, ft. :	<u>0.5</u>	Log Speed, ft/min.:	<u>n/a</u>

**Logging Operation Notes:**

This borehole was logged in three log runs. The total logging depth achieved by the SGLS was 86.5 ft.

---

**Analysis Information**

---

Analyst : S.D. BarryData Processing Reference : MAC-VZCP 1.7.9Analysis Date : 03/02/1998**Analysis Notes :**

The pre- and post-survey field verification spectra for all logging runs met the acceptance criteria established for peak shape and system efficiency. The energy calibration and peak-shape calibration from these spectra were used to establish the peak resolution and channel-to-energy parameters used in processing the spectra acquired during the logging operation.

Casing correction factors for a 0.280-in.-thick steel casing (based on a 6-in., schedule-40 pipe) were applied to the entire logged interval during the analysis process.

Shape factor analysis was applied to the SGLS data and provided insights into the distribution of Cs-137 contamination and into the nature of zones of elevated total count gamma-ray activity not attributable to gamma-emitting radionuclides.

**Log Plot Notes:**

Separate log plots show the man-made and the naturally occurring radionuclides. The natural radionuclides can be used for lithology interpretations. The headings of the plots identify the specific gamma rays used to calculate the concentrations. Uncertainty bars on the plots show the statistical uncertainties for the measurements as 95-percent confidence intervals. Open circles on the plots give the MDL. The MDL of a radionuclide represents the lowest concentration at which positive identification of a gamma-ray peak is statistically defensible.

A combination plot includes the man-made and natural radionuclides, the total gamma derived from the spectral data, and the Tank Farms gross gamma log. The gross gamma plot displays the latest available digital data. No attempt has been made to adjust the depths of the gross gamma logs to coincide with the SGLS data.

A time-sequence plot of the historical gross gamma log data from 1975 to 1992 is presented with the log plots.



Spectral Gamma-Ray Borehole  
Log Data Report

Page 3 of 3

Borehole

10-02-06

Log Event A

**Results/Interpretations:**

The only man-made radionuclide detected in this borehole was Cs-137. Cs-137 contamination was detected continuously from the ground surface to 15 ft.

At a depth of 17 ft, the K-40 concentration values increase from about 10 to 13 pCi/g.

An analysis of the shape factors associated with applicable segments of the spectra was performed. The shape factor analysis for the interval from the ground surface to about 18 ft indicates the contamination is uniformly distributed in the backfill sediments around the borehole casing.

Additional information and interpretations of log data are included in the main body of the Tank Summary Data Report for tank A-102.